WTCI-661-P

2/15/67

CHANGES TO BUILDING
TO CONFORM
TO NEW NEW YORK CITY BUILDING
CODE

1. Fire tower corridor eliminated.
2. Number of stairs reduced from 6 to 3 (Old plans had 5 stairs at 3'-8" and 1 stair at 4'8" for a total population of 390. New plans have 2 stairs at 3'-8" and 1 stair at 4'-8" allowing a population of 390).
3. The size of doors leading to the stairs are changed from 3'-8" to 3'-0".
4. All stairs exit through a lobby. Old plans had fire tower stair exiting through a fire enclosed corridor.
5. Shaft walls are changed from a 3-hour rating to a 2-hour rating.
6. Corridors are limited to a 100' dead end and with a 2-hour rating.
7. Additional [illegible] changed from 20 pounds per square foot to 6 pounds per square foot (based on partition weight of 50 pounds to 100 pounds per linear foot).

CKP/jw

File Category No.	Document Title/Format/Type	Author Organization	File Location Room	Cabinet
WTCI - 000477 - P	Correspondence Collected from Various PA Sources on Adoption of Revisions to NYC Building Code **Format:** Hard Copy **Type:** Correspondence **Classification:** Materials Agreement	PANYNJ and others	B257	40